trioctylaluminium

IDENTIFICATION NUMBERS

- **CAS:** 1070-00-4
- **EC/EINECS:** 213-964-4

MORE INFORMATION

- **Molecular Formula:** C24H51Al
- **Synonyms:** TRI-n-OCTILALUMINIO

CLASSIFICATION AND LABELLING (Regulation 1272/2008)

Symbols



GHS02

Flammable gases



GHS05

Corrosive to metals

Signal word: **Danger**

H Phrases

H250 : Catches fire spontaneously if exposed to air

Pyr. Liq. (Cat. 1) : Pyrophoric liquid

H260 : In contact with water releases flammable gases which may ignite spontaneously

Water-react. (Cat. 1) : Substance or mixture which in contact with water emits flammable gas

H314 : Causes severe skin burns and eye damage

Skin Corr. (Cat. 1B) : Skin corrosion/irritation

Notes

- R.1272-Note A

Specific health risks

Occupational Exposure Limits (OEL)

Daily exposure limit values (VLA-ED) published by the Spanish National Institute of Safety and Health at Work (INSST). They represent the average concentration of a chemical agent in the worker's breathing zone, measured or calculated in a time-weighted manner for an 8-hour daily working period. (https://www.insst.es/valores-limites-de-exposicion)

Specific environmental risks

Hazardous water substances (Germany)

Substances classified with chronic aquatic toxicity under the CLP Regulation (H410–H413 phrases, Aquatic Chronic categories 1 to 4). They pose a long-term hazard to aquatic organisms, even at low concentrations and through prolonged exposure.

MMA CLASSIFICATION

1