methyl acetate

IDENTIFICATION NUMBERS

- **CAS:** 79-20-9
- **EC/EINECS:** 201-185-2
- **International Chemical Safety Card (ICSC):** 0507

MORE INFORMATION

- **Molecular Formula:** C3H6O2

USES

solvent

CLASSIFICATION AND LABELLING (Regulation 1272/2008)

Symbols



GHS02

Flammable gases



GHS07

Acute toxicity (oral, dermal, inhalation

Signal word: **Danger**

H Phrases

H225 : Highly flammable liquid and vapour

Flam. Liq. (Cat. 2) : Flammable liquid

H319 : Causes serious eye irritation

Eye Irrit. (Cat. 2) : Serious eye damage/eye irritation

H336 : May cause drowsiness or dizziness

STOT SE (Cat. 3) : Specific target organ toxicity - single exposure

EUH066

Specific health risks

Occupational Exposure Limits (OEL)

Daily exposure limit values (VLA-ED) published by the Spanish National Institute of Safety and Health at Work (INSST). They represent the average concentration of a chemical agent in the worker's breathing zone, measured or calculated in a time-weighted manner for an 8-hour daily working period. (https://www.insst.es/valores-limites-de-exposicion)

Restriction/prohibition regulations

Major accident hazards (Seveso)

Hazardous substances listed in Annex I of the Seveso III Directive (Directive 2012/18/EU), transposed in Spain by Royal Decree 840/2015. Their presence in industrial establishments in quantities equal to or above established thresholds triggers obligations to implement major accident risk control measures.